

nextek 57

Microencapsulated Phase Change Material

Phase Change: 57°C, 134.6 °F



DESCRIPTION

nextek is the next level in PCM technology and performance. Nextek's patented capsule wall technology combines robustness, high thermal stability, and easy dispersability. It is versatile enough to be used in a variety of uses and formulations.

APPLICATIONS

The applications for phase change materials are limited only by the imagination. Some common uses for nextek PCM at this temperature include:

- **Electronics** – for cooling electrical components or maintaining constant temperatures for scientific instrumentation.

PACKAGING

This product is generally shipped in either 55-gallon fiber drums of 245 pounds net weight (175 pounds nominal dry weight) or in super sacks of 1,000 pounds (approximately 750 pounds nominal dry weight).

HEALTH AND SAFETY

Please refer to the Safety Data Sheet (SDS) for necessary safety and handling precautions for this product.

PROPERTIES

nextek 57 typically exhibits these general properties:

Typical Properties

Appearance White to slightly off-white color

Form Wet Cake ($\geq 70\%$ solids)

Particle size (mean) 25-45 micron

Melting point 57°C, 134.6°F ($\pm 2^\circ\text{C}$)

Heat of fusion ≥ 180 J/g

Visit www.microteklabs.com or call 937.236.2213 for more information on your thermal management needs.

IMPORTANT NOTE: This data has been compiled from testing that Microtek Labs believes reliable and is supplied for informational purposes only. Microtek Labs encourages purchasers to validate this data and the product's fitness for use in the purchaser's process by performing their own tests.

MT18-002 Nextek 57 PDS © 2020 Microtek Laboratories, Inc. All Rights Reserved.
All other trademarks are the properties of their respective owners.

MPDS3300-0074

Revision 1

Effective Date: 03/19/2020

microtek
laboratories, inc.