# nextek 6

Microencapsulated Phase Change Material Phase Change: 6°C, 42.8°F



nextek is the next level in PCM technology and performance. Nextek's patented capsule wall technology combines robustness, high thermal stability, and easy dispersability. It is versatile enough to be used in a variety of uses and formulations.

### **APPLICATIONS**

The applications for phase change materials are limited only by the imagination. Some common uses for nextek PCM at this temperature include:

• Packaging and Shipping – to protect temperature sensitive materials in storage and transit.

### **PACKAGING**

This product is generally shipped in either 55-gallon fiber drums of 245 pounds net weight (175 pounds nominal dry weight) or in super sacks of 1,000 pounds (approximately 750 pounds nominal dry weight).

## **HEALTH AND SAFETY**

Please refer to the Safety Data Sheet (SDS) for necessary safety and handling precautions for this product.

#### **PROPERTIES**

nextek 6 typically exhibits these general properties:

Typical Properties	
Appearance	White to slightly off-white color
Form	Wet cake (≥ 70% solids)
Particle size (mean)	14-24 micron
Melting point	6°C, 42.8°F (±2°C)
Heat of fusion	≥170 J/g

Visit www.microteklabs.com or call 937.236.2213 for more information on your thermal management needs.

IMPORTANT NOTE: This data has been compiled from testing that Microtek Labs believes reliable and is supplied for informational purposes only. Microtek Labs encourages purchasers to validate this data and the product's fitness for use in the purchaser's process by performing their own tests.

MT18\_002 Nextek 6W PDS © 2018 Microtek Laboratories, Inc. All Rights Reserved. All other trademarks are the properties of their respective owners.

MPDS3300-0047

Revision 2

Effective Date: 03/19/2020

